



Aqua Maxx

KEY FEATURES

- 100% drainage backing system - drains at 787.15 in/hr (ASTM F1551)
- Water and waste drain directly through the backing - Fast drainage and our exclusive backing reduces pet odors and kills bacteria
- Anti-Microbial Construction
- Thermally stable, wrinkle free backing
- Cooling Technology - lowers lawn surface temperature
- Created with an incredible tuft bind; dogs won't be able to dig through the extremely tough backing
- Enhanced fiber memory creating increased resilience while giving a soft feel and realistic look. Perfect for high traffic areas

TESTING SPECIFICATIONS

ASTM D1335 - Tuft Bind	12 LB
ASTM F2765 - Lead Levels	<0.01ppm
ASTM D2859 - Flammability (Pill Test)	Pass
ASTM E648 - Flammability (Critical Radiant Flux)	Pass
ASTM 5034 - Grab Tear Strength	Pass
ASTM F1951 - ADA Wheelchair	Compliant
ASTM F1551 - Water Permeability	787.15 in/hr
ASTM 1292 - Impact Attenuation	Pass

Yarn Type.....	Polyethylene Monofilament
Thatch.....	Polypropylene
Yarn Color.....	Sport, Apple, & Olive Green
Thatch Color.....	Field Green & Tan
Face Weight.....	50 oz/sy
Pile Height.....	1"
Yarn Denier.....	990/9-1100
Backing.....	Anti-Microbial Urethane
Width.....	15 ft
Warranty.....	15-Year Warranty

Recommended Infill

Type:.....	Spherical Infill
Weight:.....	2 - 2.5 lbs per sq ft
Height:.....	.1/2 in
Maintenance: Rinse and groom as needed to limit matting	

For Installation Information Contact

Synthetic Grass Pros
10550 Maybank Drive
Dallas, TX 75220
972.420.7800

SyntheticGrassPros.com