



# Platinum HeatMaxx 65

- Warranted against reflective burns from Low-E windows
- Rooftop use - ASTM E108, Class A
- Indoor use - ASTM E85
- 100% nylon face yarns - delivers superior performance

Recommended Use: Heavy Traffic  
Main Application: Landscape  
Colors: Jade / Spring Green

Yarn Characteristics  
Type: Nylon / Polypropylene  
Yarn Denier: 8,800 / 8  
Thatch Denier: 1,100

Backing Characteristics  
Primary Backing 1  
Composition/Structure: Black Urethane  
Weight: 22 oz

Primary Backing 2  
Composition/Structure: Urethane  
Weight: Pic 7

Total Product Weight: 93 oz / yd  
Face Weight: 65 oz  
Pile Height: 1.5 in  
Machine Gauge: 3/8  
Thatch Color: Sandstone / Olive

Width: 15 ft  
Length: 100 ft  
Shipping Weight: 981 lbs  
Drainage Rate: 28+ inch per sq yd

Warranty: 10 Year

TUFT BIND	16.5 lbs	ASTM D1335
FLAMMABILITY (PILL TEST)	Pass	ASTM D2859
FLAMMABILITY (CRITICAL RADIANT FLUX)	Pass	ASTM E648
GRAB TEAR STRENGTH	Pass	ASTM 5034
ADA WHEELCHAIR	Compliant	ASTM F1951
WATER PERMEABILITY	442.68 in/hr	ASTM F1551
FIRE TEST (ROOF DECKS)	Class A	ASTM E108
SMOKE DENSITY	Class C	ASTM E84

**Recommended Infill**

Type: Spherical Infill  
Weight: 2.0 - 2.5 lbs per sq ft  
Height: 1/2 in

Maintenance: Rinse and groom as needed to limit matting

Synthetic Grass Pros  
10550 Maybank Drive  
Dallas, TX 75220  
972.420.7800

Synthetic Grass Pros  
9705 Port Erroll Dr.  
Houston, TX 77095  
713.487.0945

For Installation Information Contact  
[SyntheticGrassPros.com](http://SyntheticGrassPros.com)